



Stainless Pipe Dimensions & Weight SCH 5 to SCH 40

Nominal Pipe Size	Nominal O.D.	Data	5s	True 5	10s	True 10	20	30	SCH 40/STD	True SCH 40
1/8	0.405	Wall Thick.		.035	.049	.049			.067	.068
		Wt/Ft.		.1383	.1863	.1863			.2447	.2447
1/4	0.54	Wall Thick.		.049	.065	.065			.088	.088
		Wt/Ft.		.2570	.3297	.3297			.4248	.4248
3/8	0.675	Wall Thick.		.049	.065	.065			.091	.091
		Wt/Ft.		.3276	.4235	.4235			.5676	.5676
1/2	0.84	Wall Thick.	.065	.065	.083	.083			.109	.109
		Wt/Ft.	.538	.538	.671	.671			.851	.851
3/4	1.05	Wall Thick.	.065	.065	.083	.083			.113	.113
		Wt/Ft.	.684	.684	.857	.857			1.131	1.131
1	1.315	Wall Thick.	.065	.065	.109	.109			.133	.133
		Wt/Ft.	.868	.868	1.404	1.404			1.679	1.679
1 1/4	1.66	Wall Thick.	.065	.065	.109	.109			.140	.140
		Wt/Ft.	1.107	1.107	1.806	1.806			2.273	2.273
1 1/2	1.9	Wall Thick.	.065	.065	.109	.109			.145	.145
		Wt/Ft.	1.274	1.274	2.085	2.085			2.718	2.718
2	2.375	Wall Thick.	.065	.065	.109	.109			.154	.154
		Wt/Ft.	1.604	1.604	2.638	2.638			3.653	3.653
2 1/2	2.875	Wall Thick.	.083	.083	.120	.120			.203	.203
		Wt/Ft.	2.475	2.475	3.531	3.531			5.793	5.793
3	3.5	Wall Thick.	.083	.083	.120	.120			.216	.216
		Wt/Ft.	3.029	3.029	4.332	4.332			7.576	7.576
3 1/2	4	Wall Thick.	.083	.083	.120	.120			.226	.226
		Wt/Ft.	3.472	3.472	4.973	4.973			9.109	9.109



COONEY BROTHERS, INC.
PIPE VALVES FITTINGS

CONTACT US

Cooney Brothers, Inc.
 1850 Gravers Road, #100
 Plymouth Meeting, PA 19462-2837
 Phone: 610-272-2100

Nominal Pipe Size	Nominal O.D.	Data	5s	True 5	10s	True 10	20	30	SCH 40/STD	True SCH 40
4	4.5	Wall Thick.	.083	.083	.120	.120			.237	.237
		Wt/Ft.	3.915	3.915	5.613	5.613			10.79	10.79
4 1/2	5	Wall Thick.							0.247	
		Wt/Ft.							12.53	
5	5.563	Wall Thick.	.109	.109	.134	.134			.258	.258
		Wt/Ft.	6.35	6.35	7.77	7.77			14.62	14.62
6	6.625	Wall Thick.	.109	.109	.134	.134			.280	.280
		Wt/Ft.	7.59	7.59	9.29	9.29			18.97	18.97
7	7.625	Wall Thick.							.301	
		Wt/Ft.							23.57	
8	8.625	Wall Thick.	.109	.109	.148	.148	.250	.277	.322	.322
		Wt/Ft.	9.91	9.91	13.40	13.40	22.36	24.70	28.55	28.55
9	9.625	Wall Thick.							.342	
		Wt/Ft.							33.90	
10	10.75	Wall Thick.	.134	.134	.165	.165	.250	.307	.365	.365
		Wt/Ft.	15.19	15.19	18.65	18.70	28.04	34.24	40.48	40.48
11	11.75	Wall Thick.							.375	
		Wt/Ft.							45.55	
12	12.75	Wall Thick.	.156	.165	.180	.180	.250	.330	.375	.406
		Wt/Ft.	21.07	22.18	24.16	24.20	33.38	43.77	49.56	53.53
14	14	Wall Thick.	.156		.188	.250	.312	.375	.375	.437
		Wt/Ft.	23.07		27.73	36.71	45.68	54.57	54.57	63.37
16	16	Wall Thick.	.165		.188	.250	.312	.375	.375	.500
		Wt/Ft.	27.90		31.75	42.05	52.36	62.58	62.58	82.77
18	18	Wall Thick.	.165		.188	.250	.312	.437	.375	.562
		Wt/Ft.	31.43		35.76	47.39	59.03	82.06	70.59	104.80
20	20	Wall Thick.	.188		.218	.250	.375	.500	.375	.594
		Wt/Ft.	39.78		46.05	52.73	78.60	104.10	78.60	122.90



COONEY BROTHERS, INC.
PIPE VALVES FITTINGS

CONTACT US

Cooney Brothers, Inc.
 1850 Gravers Road, #100
 Plymouth Meeting, PA 19462-2837
 Phone: 610-272-2100

Nominal Pipe Size	Nominal O.D.	Data	5s	True 5	10s	True 10	20	30	SCH 40/STD	True SCH 40
22	22	Wall Thick.				.250	.375	.500	.375	
		Wt/Ft.				58.07	86.61	114.81	86.61	
24	24	Wall Thick.	.218		.250	.250	.375	.562	.375	.687
		Wt/Ft.	55.37		63.41	63.41	94.62	140.80	94.62	171.20
26	26	Wall Thick.				.312			.375	
		Wt/Ft.				85.73			102.63	
30	30	Wall Thick.	.250		.312	.312		.625	.375	
		Wt/Ft.	79.43		98.93	99.08		196.08	118.65	
34	34	Wall Thick.				.312		.625	.375	.688
		Wt/Ft.				112.43		222.78	134.67	244.60
36	36	Wall Thick.				.312		.625	.375	.688
		Wt/Ft.				119.11		236.13	142.68	282.36
42	42	Wall Thick.						.625	.375	.688
		Wt/Ft.						276.17	166.71	330.41