



## Steel Pipe Dimensions and Weights SCH 5 to SCH 40

Nominal Pipe Size	Nominal O.D.	Data	Sch. 5S	Sch. 5	Sch.10S	True Sch. 10	Sch. 20	Sch. 30	Sch. 40/STD	True Sch. 40
1/8"	0.405	Wall Thick.		.035	.049	.049			.068	.068
		Wt/Ft.		.138	.186	.186			.245	.245
1/4"	0.54	Wall Thick.		.049	.065	.065			.088	.088
		Wt/Ft.		.257	.330	.330			.425	.425
3/8"	0.675	Wall Thick.		.049	.065	.065			.091	.091
		Wt/Ft.		.328	.424	.424			.568	.568
1/2"	0.84	Wall Thick.	.065	.065	.083	.083			.109	.109
		Wt/Ft.	.538	.538	.671	.671			.851	.851
3/4"	1.05	Wall Thick.	.065	.065	.083	.083			.113	.113
		Wt/Ft.	.684	.684	.857	.857			1.131	1.131
1"	1.315	Wall Thick.	.065	.065	.109	.109			.133	.133
		Wt/Ft.	.868	.868	1.404	1.404			1.679	1.679
1-1/4"	1.66	Wall Thick.	.065	.065	.109	.109			.140	.140
		Wt/Ft.	1.107	1.107	1.806	1.806			2.273	2.273
1-1/2"	1.9	Wall Thick.	.065	.065	.109	.109			.145	.145
		Wt/Ft.	1.274	1.274	2.085	2.085			2.718	2.718
2"	2.375	Wall Thick.	.065	.065	.109	.109			.154	.154
		Wt/Ft.	1.604	1.604	2.638	2.638			3.653	3.653
2-1/2"	2.875	Wall Thick.	.083	.083	.120	.120			.203	.203
		Wt/Ft.	2.475	2.475	3.531	3.531			5.793	5.793
3"	3.5	Wall Thick.	.083	.083	.120	.120			.216	.216
		Wt/Ft.	3.029	3.029	4.332	4.332			7.576	7.576
3-1/2"	4	Wall Thick.	.083	.083	.120	.120			.226	.226
		Wt/Ft.	3.472	3.472	4.937	4.937			9.109	9.109



**COONEY BROTHERS, INC.**  
**PIPE VALVES FITTINGS**

**CONTACT US**

Cooney Brothers, Inc.  
 1850 Gravers Road, #100  
 Plymouth Meeting, PA 19462-2837  
 Phone: 610-272-2100

Nominal Pipe Size	Nominal O.D.	Data	Sch. 5S	Sch. 5	Sch.10S	True Sch. 10	Sch. 20	Sch. 30	Sch. 40/STD	True Sch. 40
4"	4.5	Wall Thick.	.083	.083	.120	.120			.237	.237
		Wt/Ft.	3.915	3.915	5.613	5.613			10.79	10.79
5"	5.563	Wall Thick.	.109	.109	.134	.134			.258	.258
		Wt/Ft.	6.349	6.349	7.770	7.770			14.62	14.62
6"	6.625	Wall Thick.	.109	.109	.134	.134			.280	.280
		Wt/Ft.	7.585	7.585	9.289	9.289			18.97	18.97
7"	7.625	Wall Thick.							.310	.310
		Wt/Ft.							23.57	23.57
8"	8.625	Wall Thick.	.109	.109	.148	.148	.250	.277	.322	.322
		Wt/Ft.	9.91	9.91	13.40	13.40	22.36	24.70	28.55	28.55
9"	9.625	Wall Thick.							.342	.342
		Wt/Ft.							33.90	33.90
10"	10.75	Wall Thick.	.134	.134	.165	.165	.250	.307	.365	.365
		Wt/Ft.	15.19	15.19	18.65	18.65	28.04	34.24	40.48	40.48
11"	11.75	Wall Thick.							.375	
		Wt/Ft.							45.55	
12"	12.75	Wall Thick.	.156	.165	.180	.180	.250	.330	.375	.406
		Wt/Ft.	21.07	22.18	24.16	24.16	33.38	43.77	49.56	53.52
14"	14	Wall Thick.	.156		.188	.250	.312	.375	.375	.438
		Wt/Ft.	23.07		27.73	36.71	45.61	54.57	54.57	63.44
16"	16	Wall Thick.	.165		.188	.250	.312	.375	.375	.500
		Wt/Ft.	27.90		31.75	42.05	52.27	62.58	62.58	82.77
18"	18	Wall Thick.	.165		.188	.250	.312	.438	.375	.562
		Wt/Ft.	31.43		35.76	47.39	58.94	82.15	70.59	104.70
20"	20	Wall Thick.	.188		.218	.250	.375	.500	.375	.594
		Wt/Ft.	39.78		46.05	52.73	78.60	104.10	78.60	123.10
22"	22	Wall Thick.			.250		.375	.500	.375	
		Wt/Ft.			58.07		86.61	114.81	86.61	



**COONEY BROTHERS, INC.**  
**PIPE VALVES FITTINGS**

**CONTACT US**

Cooney Brothers, Inc.  
 1850 Gravers Road, #100  
 Plymouth Meeting, PA 19462-2837  
 Phone: 610-272-2100

Nominal Pipe Size	Nominal O.D.	Data	Sch. 5S	Sch. 5	Sch. 10S	True Sch. 10	Sch. 20	Sch. 30	Sch. 40/STD	True Sch. 40
24"	24	Wall Thick.	.218		.250	.250	.375	.562	.375	.688
		Wt/Ft.	55.37		63.41	63.41	96.42	140.70	94.62	171.30
26"	26	Wall Thick.				.312	.500		.375	
		Wt/Ft.				85.60	136.17		102.63	
28"	28	Wall Thick.				.312	.500	.625	.375	
		Wt/Ft.				92.26	146.85	182.73	110.64	
30"	30	Wall Thick.	.250		.312	.312	.500	.625	.375	
		Wt/Ft.	79.43		98.93	98.93	157.53	196.08	118.65	
32"	32	Wall Thick.				.312	.500	.625	.375	.688
		Wt/Ft.				105.59	168.21	209.43	126.66	230.06
34"	34	Wall Thick.				.312	.500	.625	.375	.688
		Wt/Ft.				112.25	178.89	222.78	134.67	244.77
36"	36	Wall Thick.				.312		.625	.375	.750
		Wt/Ft.				118.92		236.13	142.68	282.35
42"	42	Wall Thick.						.625	.375	.750
		Wt/Ft.						276.18	166.71	330.41
48"	48	Wall Thick.							.375	
		Wt/Ft.							190.74	