



Steel Pipe Dimensions and Weights SCH 60 to XXH

Nominal Pipe Size	Nominal O.D.	Data	Sch. 60	Sch. 80/XH	True Sch. 80	Sch. 100	Sch. 120	Sch. 140	Sch. 160	XXH
1/8"	0.405	Wall Thick.		.095	.095					
		Wt/Ft.		.315	.315					
1/4"	0.54	Wall Thick.		.119	.119					
		Wt/Ft.		.535	.535					
3/8"	0.675	Wall Thick.		.126	.126					
		Wt/Ft.		.739	.739					
1/2"	0.84	Wall Thick.		.147	.147				.187	.294
		Wt/Ft.		1.088	1.088				1.304	1.714
3/4"	1.05	Wall Thick.		.154	.154				.218	.308
		Wt/Ft.		1.474	1.474				1.937	2.441
1"	1.315	Wall Thick.		.179	.179				.250	.358
		Wt/Ft.		2.172	2.172				2.844	3.659
1-1/4"	1.66	Wall Thick.		.191	.191				.250	.382
		Wt/Ft.		2.997	2.997				3.765	5.214
1-1/2"	1.9	Wall Thick.		.200	.200				.281	.400
		Wt/Ft.		3.631	3.631				4.859	6.408
2"	2.375	Wall Thick.		.218	.218				.344	.436
		Wt/Ft.		5.022	5.022				7.462	9.029
2-1/2"	2.875	Wall Thick.		.276	.276				.375	.552
		Wt/Ft.		7.661	7.661				10.01	13.70
3"	3.5	Wall Thick.		.300	.300				.438	.600
		Wt/Ft.		10.25	10.25				14.32	18.58
3-1/2"	4	Wall Thick.		.318	.318					.636



COONEY BROTHERS, INC.
PIPE VALVES FITTINGS

CONTACT US
Cooney Brothers, Inc.
1850 Gravers Road, #100
Plymouth Meeting, PA 19462-2837
Phone: 610-272-2100
www.cooneybrothers.com

Nominal Pipe Size	Nominal O.D.	Wt/Ft. Data	Sch. 60	Sch. 80/XH	True Sch. 80	Sch. 100	Sch. 120	Sch. 140	Sch. 160	XXH
4"	4.5	Wall Thick.		.337	.337		.438		.531	.674
		Wt/Ft.		14.98	14.98		19.00		22.51	27.54
5"	5.563	Wall Thick.		.375	.375		.500		.625	.750
		Wt/Ft.		20.78	20.78		27.04		32.96	38.55
6"	6.625	Wall Thick.		.432	.432		.562		.719	.864
		Wt/Ft.		28.57	28.57		36.39		43.35	53.16
7"	7.625	Wall Thick.		.500	.500					.875
		Wt/Ft.		38.05	38.05					63.08
8"	8.625	Wall Thick.	.406	.500	.500	.594	.719	.812	.906	.875
		Wt/Ft.	35.64	43.39	43.39	50.95	60.71	67.76	74.79	72.42
9"	9.625	Wall Thick.		.500	.500					0.875
		Wt/Ft.		48.72	48.72					81.77
10"	10.75	Wall Thick.	.500	.500	.594	.719	.844	1.000	1.125	1.000
		Wt/Ft.	54.74	54.74	64.43	77.03	82.29	104.10	115.60	104.10
11"	11.75	Wall Thick.		.500						0.875
		Wt/Ft.		60.07						101.63
12"	12.75	Wall Thick.	.562	.500	.688	.844	1.000	1.125	1.312	1.000
		Wt/Ft.	73.15	65.42	88.63	107.30	125.50	136.70	160.30	125.50
14"	14	Wall Thick.	.594	.500	.750	.938	1.094	1.250	1.406	
		Wt/Ft.	85.05	72.09	106.10	130.90	150.80	170.20	189.10	
16"	16	Wall Thick.	.656	.500	.844	1.031	1.219	1.438	1.594	
		Wt/Ft.	107.50	82.77	136.60	164.80	192.40	223.60	245.30	
18"	18	Wall Thick.	.750	.500	.938	1.156	1.375	1.562	1.781	
		Wt/Ft.	138.20	93.45	170.90	208.00	244.10	274.20	308.50	
20"	20	Wall Thick.	.812	.500	1.031	1.281	1.500	1.750	1.969	
		Wt/Ft.	166.40	104.10	208.90	256.10	296.40	341.10	379.20	



COONEY BROTHERS, INC.
PIPE VALVES FITTINGS

CONTACT US
 Cooney Brothers, Inc.
 1850 Gravers Road, #100
 Plymouth Meeting, PA 19462-2837
 Phone: 610-272-2100
www.cooneybrothers.com

22"	22	Wall Thick.		.500		1.375	1.625	1.875	2.125	
		Wt/Ft.		114.81		302.88	353.61	403.00	451.06	
Nominal Pipe Size	Nominal O.D.	Data	Sch. 60	Sch. 80/XH	True Sch. 80	Sch. 100	Sch. 120	Sch. 140	Sch. 160	XXH
24"	24	Wall Thick.	.969	.500	1.219	1.531	1.812	2.062	2.344	
		Wt/Ft.	238.40	125.50	296.60	367.40	429.40	483.10	542.10	
26"	26	Wall Thick.		.500						
		Wt/Ft.		136.17						
28"	28	Wall Thick.								
		Wt/Ft.								
30"	30	Wall Thick.		.500						
		Wt/Ft.		157.53						
32"	32	Wall Thick.		.500						
		Wt/Ft.		168.21						
34"	34	Wall Thick.								
		Wt/Ft.								
36"	36	Wall Thick.		.500						
		Wt/Ft.		189.57						
42"	42	Wall Thick.		.500						
		Wt/Ft.		221.61						
48"	48	Wall Thick.		.500						
		Wt/Ft.		253.65						