## HANGER RODS



# Fig. 146

### **Continuous Threaded Rod**

**Size Range:**  $\frac{1}{4}$ " through  $1\frac{1}{2}$ " Stocked in six, ten, and twelve foot lengths. Other even foot lengths can be furnished to order.


Material: Carbon steel or Stainless Steel Gr 304

**Threads:** National Coarse (USS), rod threaded complete length. **Finish:** Plain or Dirac Zinc Plated (Hot-Dip Galvanized optional)

#### Maximum Temperature: 650° F.

**Ordering:** Specify rod diameter and length, figure number, name and finish.

**Note:** The acceptability of galvanized coatings at temperatures above 450°F is at the discretion of the end user.



#### 

FIG. 146: OADS (LBS) • WEIGHTS (LBS) • DIMENSIONS (IN				
Rod Size A	Threads per Inch	Max Load 650° F	Weight per Ft.	
1⁄4	20	240	0.12	
3⁄8	16	730	0.30	
1/2	13	1,350	0.53	
5/8	11	2,160	0.84	
3⁄4	10	3,230	1.20	
7/8	9	4,480	1.70	
1	8	5,900	2.30	
<b>1</b> <sup>1</sup> ⁄ <sub>4</sub>	7	9,500	3.60	
<b>1</b> ½	6	13,800	5.10	

Note: Other rod sizes available upon request. Class 2 fit is available upon request.

PROJECT INFORMATION	APPROVAL STAMP
Project:	Approved
Address:	Approved as noted
Contractor:	🔲 Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	
PH-1.15	· · · ·