

FIG. 7053

11 1/4° Elbow




FIGURE 7053 11 1/4° ELBOW			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	1 3/8	0.3
25	33.4	35	0.1
1 1/4	1.660	1 3/8	0.5
32	42.2	35	0.2
1 1/2	1.900	1 3/8	0.7
40	48.3	35	0.3
2	2.375	1 3/8	0.9
50	60.3	35	0.4
2 1/2	2.875	1 1/2	1.5
65	73.0	38	0.7
3	3.500	1 1/2	2.0
80	88.9	38	0.9
3 1/2	4.000	1 3/4	2.8
90	101.6	44	1.3
4	4.500	1 3/4	3.3
100	114.3	44	1.5
5	5.563	2	5.0
125	141.3	51	2.3
6	6.625	2	6.5
150	168.3	51	2.9
8	8.625	2	10.0
200	219.1	51	4.5
10	10.750	2 1/8	14.5
250	273.1	54	6.6
12	12.750	2 1/4	18.7
300	323.9	57	8.5
14	14.000	3 1/2	32.1
350	355.6	89	14.6
16	16.000	4	42.0
400	406.4	102	19.1
18	18.000	4 1/2	53.2
450	457.2	114	24.1
20	20.000	5	65.7
500	508.0	127	29.8
24	24.000	6	96.0
600	609.6	152	43.5

FIG. 7050LR

90° Long Radius Elbow




FIGURE 7050 LR LONG RADIUS 90° ELBOW			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	3 1/2	0.9
25	33.4	89	0.4
1 1/4	1.660	3 7/8	1.3
32	42.2	98	0.6
1 1/2	1.900	4 1/4	1.7
40	48.3	108	0.8
2	2.375	4 3/8 C	2.5
50	60.3	111	1.1
2 1/2	2.875	5 3/4	4.9
65	73.0	146	2.2
3	3.500	5 7/8 C	6.5
80	88.9	149	2.9
3 1/2	4.000	7 1/4	9.7
90	101.6	184	4.4
4	4.500	7 1/2	11.5
100	114.3	191	5.2
5	5.563	9 1/2	20.9
125	141.3	241	9.5
6	6.625	10 3/4	29.1
150	168.3	273	13.2
8	8.625	15	59.2
200	219.1	381	26.9
10	10.750	18	104.0
250	273.1	457	47.2
12	12.750	21	147.0
300	323.9	533	66.7
14	14.000	21 C	176.0
350	355.6	533	79.8
16	16.000	24 C	230.0
400	406.4	610	104.3
18	18.000	27 C	293.0
450	457.2	686	132.9
20	20.000	30 C	362.0
500	508.0	762	164.2
24	24.000	36 C	520.0
600	609.6	914	235.9

FIG. 7051LR

45° Long Radius Elbow




FIGURE 7051 LR LONG RADIUS 45° ELBOW			
Nominal Size	O.D.	Center to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1	1.315	2 1/2	0.7
25	33.4	64	0.3
1 1/4	1.660	2 1/2	1.0
32	42.2	64	0.5
1 1/2	1.900	2 1/2	1.2
40	48.3	64	0.5
2	2.375	2 3/4	1.7
50	60.3	70	0.8
2 1/2	2.875	3	2.9
65	73.0	76	1.3
3	3.500	3 3/8	4.3
80	88.9	86	2.0
3 1/2	4.000	3 1/2	5.3
90	101.6	89	2.4
4	4.500	4	7.2
100	114.3	102	3.3
5	5.563	5	12.2
125	141.3	127	5.5
6	6.625	5 1/2	17.4
150	168.3	140	7.9
8	8.625	7 1/4	34.0
200	219.1	184	15.4
10	10.750	8 1/2	57.4
250	273.1	216	26.0
12	12.750	10	82.6
300	323.9	254	37.5
14	14.000	8 3/4 C	89.0
350	355.6	222	40.4
16	16.000	10 C	125.0
400	406.4	254	56.7
18	18.000	11 1/4 C	158.0
450	457.2	286	71.7
20	20.000	12 1/2 C	194.0
500	508.0	317	88.0
24	24.000	15 C	277.0
600	609.6	381	125.6

C - Cast ductile iron, all others are fabricated steel.

Center to end dimensions and weights may differ from those shown in chart, Contact an Anvil Representative for more information.



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.


PROJECT INFORMATION		APPROVAL STAMP	
Project:		☐ Approved	
Address:		☐ Approved as noted	
Contractor:		☐ Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			

Gruvlok fittings are available through 24" nominal pipe size in a variety of styles. Use the Fitting Size Table to convert nominal pipe size to corresponding pipe O.D.

These fittings are designed to provide minimum pressure drop and uniform strength.

Depending on styles and size, Gruvlok fittings are provided in various materials including ductile iron, forged steel or fabricated steel.

Pressure ratings of Gruvlok standard fittings conform to those of Fig. 7001 Gruvlok coupling.



FLOW DATA – FRICTIONAL RESISTANCE (EXPRESSED AS EQUIVALENT STRAIGHT PIPE)

Nom. Size	O.D.	Pipe Wall Thickness	Elbow		Tee	
			90°	45°	Branch	Run
In./DN(mm)	In./mm	In./mm	ft./m	ft./m	ft./m	ft./m
1	1.315	0.133	1.7	0.9	4.4	1.7
25	33.4	3.4	0.5	0.3	1.3	0.5
1 1/4	1.660	0.140	2.3	1.2	5.8	2.3
32	42.2	3.6	0.7	0.4	1.8	0.7
1 1/2	1.900	0.145	2.7	1.3	6.7	2.7
40	48.3	3.7	0.8	0.4	2.0	0.8
2	2.375	0.154	3.4	1.7	8.6	3.4
50	60.3	3.9	1.0	0.5	2.6	1.0
2 1/2	2.875	0.203	4.1	2.1	10.3	4.1
65	73.0	5.2	1.2	0.6	3.1	1.2
3 O.D.	2.996	0.197	4.3	2.2	10.8	4.3
76.1	76.1	5.0	1.3	0.7	3.3	1.3
3	3.500	0.216	5.1	2.6	12.8	5.1
80	88.9	5.5	1.6	0.8	3.9	1.6
4 1/4 O.D.	4.250	0.220	6.4	3.2	16.1	6.4
108.0	108.0	5.6	2.0	1.0	4.9	2.0
4	4.500	0.237	6.7	3.4	16.8	6.7
100	114.3	6.0	2.0	1.0	5.1	2.0
5 1/4 O.D.	5.236	0.248	8.0	4.0	20.1	8.0
133.0	133.0	6.3	2.4	1.2	6.1	2.4
5 1/2 O.D.	5.500	0.248	8.3	4.2	20.9	8.3
139.7	139.7	6.3	2.5	1.3	6.4	2.5
5	5.563	0.258	8.4	4.2	21.0	8.4
125	141.3	6.6	2.6	1.3	6.4	2.6
6 1/4 O.D.	6.259	0.280	9.7	4.9	24.3	9.7
159.0	159.0	7.1	3.0	1.5	7.4	3.0
6 1/2 O.D.	6.500	0.280	10.0	5.0	24.9	10.0
165.1	165.1	7.1	3.0	1.5	7.6	3.0
6	6.625	0.280	10.1	5.1	25.3	10.1
150	168.3	7.1	3.1	1.6	7.7	3.1
8	8.625	0.322	13.3	6.7	33.3	13.3
200	219.1	8.2	4.1	2.0	10.1	4.1
10	10.750	0.365	16.7	8.4	41.8	16.7
250	273.1	9.3	5.1	2.6	12.7	5.1
12	12.750	0.375	20.0	10.0	50.0	20.0
300	323.9	9.5	6.1	3.0	15.2	6.1
14	14.000	0.375	22.2	11.7	64.2	22.9
350	355.6	9.5	6.8	3.4	19.6	7.0
16	16.000	0.375	25.5	12.4	73.9	26.4
400	406.4	9.5	7.8	4.0	22.5	8.0
18	18.000	0.375	28.9	14.1	87.2	31.1
450	457.2	9.5	8.8	4.4	26.6	9.5
20	20.000	0.375	32.2	15.7	97.3	34.8
500	508.0	9.5	9.8	4.9	29.7	10.6
24	24.000	0.375	38.9	19.1	113.0	40.4
600	609.6	9.5	11.9	5.9	34.4	12.3

For the reducing tee and branches, use the value that is corresponding to the branch size. For example: for 6" x 6" x 3" tee, the branch value of 3" is 12.8 ft (3.9).

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile iron conforming to ASTM A 536, Grade 65-45-12

Malleable iron conforming to ASTM A 47

FABRICATED FITTINGS:

1-12" Carbon steel, Schedule 40, conforming to ASTM A 53, Grade B

14-24" Carbon steel, 0.375 wall, conforming to ASTM A 53, Grade B

COATINGS:

Rust inhibiting paint – Color: ORANGE (standard)

Hot Dipped Zinc Galvanized conforming to ASTM A 153 (optional)

Other Colors Available (IE: RAL3000 and RAL9000)

FITTING SIZE

Nominal Size	O.D.	Nominal Size	O.D.
In./DN(mm)	In./mm	In./DN(mm)	In./mm
1	1.315	5	5.563
25	33.4	140	141.3
1 1/4	1.660	6 1/4 O.D.	6.259
32	42.4	159.0	159.0
1 1/2	1.900	6 1/2 O.D.	6.500
40	48.3	165.1	165.1
2	2.375	6	6.625
50	60.3	150	168.3
2 1/2	2.875	8	8.625
65	73.0	200	219.1
3 O.D.	2.996	10	10.750
76.1	76.1	250	273.0
3	3.500	12	12.750
80	88.9	300	323.9
3 1/2	4.000	14	14.000
90	101.6	350	355.6
4 1/4 O.D.	4.250	16	16.000
108.0	108.0	400	406.4
4	4.500	18	18.000
100	114.3	450	457.2
5 1/4 O.D.	5.236	20	20.000
133.0	133.0	500	508.0
5 1/2 O.D.	5.500	24	24.000
139.7	139.7	600	609.6

The Fitting Size Chart is used to determine the O.D. of the pipe that the fittings is to be used with. Gruvlok Fittings are identified by either the Nominal size in inches or the Pipe O.D. in/mm.