

STAINLESS STEEL METHOD



GRUVLOK STAINLESS STEEL FITTINGS - TYPE 316

Gruvlok Schedule 10 Stainless Steel Fittings are segmentally welded with ends grooved to Gruvlok specifications. The standard material is 316 Stainless Steel unless otherwise noted with 304SS and/or Schedule 40 optional. Installation is quick and easy with the Gruvlok Figure 7400SS Coupling, or other Gruvlok product.

☐ FIG. 7050SS

90° Stainless Steel Elbow Type 316





FIG	IURE 705 0	OSS
90° STAII	NLESS STEE	L ELBOW
	1	

Nominal Size	Center to End*	Approx. Wt. Ea.
In./DN(mm)	In./mm	Lbs./Kg
11/4	35/8	1.2
32	98	0.5
11/2	41/4	1.4
40	108	0.6
2	43//8	2.3
50	111	1.0
2 ½	5 ³ / ₄	3.3
65	146	1.5
3	5 ⁷ /8	4.6
80	149	2.1
4	71/2	7.9
100	191	3.6
6	10 ³ / ₄	17.0
150	273	7.7
8	15	29.4
200	381	13.4
10	18	41.8
250	457	18.9
12	21	46.5

☐ FIG. 7051SS

45° Stainless Steel Elbow Type 316



	FIGL	JRE	705	155	
45° S	TAINL	ESS	STEE	L EL	BOW

Nominal	Center	Approx.
Size	to End*	Wt. Ea.
In./DN(mm)	In./mm	Lbs./Kg
1½	2½	0.7
32	64	0.3
1½	2½	0.9
40	64	0.4
2	2 ¹ / ₂	1.5
50	64	0.7
2½	3	1.9
65	76	0.9
3	33/8	3.3
80	86	1.5
4	4	5.4
100	102	2.4
6	5 ¹ / ₂	11.2
150	140	5.1
8 200	7 ¹ / ₄ 184	19.8 9.0
10	8 ¹ / ₂	21.0
250	216	9.5
12	10	23.0

☐ FIG. 7060SS

Stainless Steel Tees Type 316




FIGURE 7060SS

STAINLESS STEEL TEE			
Nominal	Center	Approx.	
Size	to End*	Wt. Ea.	
In./DN(mm)	In./mm	Lbs./Kg	
1½	2 ³ / ₄	1.5	
32	70	0.7	
1½	2 ³ / ₄	1.8	
40	70	0.8	
2	3 ¹ / ₄	2.4	
50	83	1.1	
2 ¹ / ₂	3 ³ / ₄	4.0	
65	95	1.8	
3	4 ¹ / ₄	5.8	
80	108	2.6	
4	5	10.3	
100	127	4.7	
6	6½	25.7	
150	165	11.7	
8 200	7 3/4 197	41.1 18.6	
10	9	36.0	
250	229	16.3	
12	10	48.4	
300	254	22.0	

☐ FIG. 7074SS

Stainless Steel Caps Type 316



FIGURE 7074SS STAINLESS STEEL CAP		
Nominal Size	Center to End*	Approx. Wt. Ea.
In./DN(mm)	In./mm	Lbs./Kg
1½ 32	15/8 41	0.4 0.2
1½ 40	15/8 41	0.5 0.2
2 50	15/8 41	0.8 0.4
2½ 65	1 ³ / ₄ 45	1.1 <i>0.5</i>
3 80	1 ³ / ₄ 45	1.6 0.7
4 100	1 ³ / ₄ 45	2.8 1.3
6 150	17/8 48	3.7 1.7
8 200	2 ¹ / ₄	8.8 4.0
10 250	2 ¹ / ₄	12.1 5.5
12 300	2 ¹ / ₄	17.3 7.8





- 1) *Dimensions may differ from those shown above. Contact an Anvil Representative for more information.
- 2) Fabricated fittings weights are based on Schedule 10 pipe.
- 3) Fabricated Schedule 10, 316SS and Schedule 40 Center to End dimensions are the same.
- 4) The pressure rating for the Gruvlok Schedule 10 Stainless Steel Fittings are equal to the pressure rating of the coupling used on Schedule 10 pipe as shown in the Working Pressure Ratings Chart for Stainless Steel Roll Grooved Pipe on page 169.

Center to End dimensions differ from the 304 A Series, when ordering verify if 304 dimensions are required.

PROJECT INFORMATION	APPROVAL STAMP
Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	