

**OPTIONS****Flush Volume**

- 1.6 gpf (6.0 Lpf) (1.6)
- 3.5 gpf (13.2 Lpf) (3.5)
- 1.28 gpf (4.8 Lpf) (1.28)
- 2.4 gpf (9.1 Lpf) (2.4)

**Finish**

- Polished Chrome (CP)
- Brushed Nickel (BN)
- Brushed Stainless (SF)
- Polished Brass (PB)

**Water Efficiency**

- Low Consumption
- Water Saver
- High Efficiency

**Handle**

- Front of Valve (H)
- Sanigard® (SG)
- Nickel-Silver (YA)

**Push Button**

- 3" Metal Oscillating (L3)
- Front of Valve (HL3)

**Control Stop**

- No (XD)
- 1" Straight (E)
- Less (L/STOP)

**Tailpiece**

- H551A 3 1/16" (H551A-3-1/16)
- H551A 4 1/16" (H551A-4-1/16)

**Inlet**

- Left of Valve (C)

**Vacuum Breaker**

- Less (XYV)

**Offset**


- 1 ½" (38mm) (1-1/2-OFST)
- 2" (51mm) (2-OFST)
- 1" (25mm) (1-OFST)

**Outlet Tube**

- Trap Primer (TP)

**Bumper**

- Double Wall (YI)

**DESCRIPTION**

Royal® Exposed Manual Water Closet Flushometer

**FEATURES**

- Flush volumes start as low as 1.28 gpf/4.8 Lpf
- Water conservation is aided by the ADA-compliant, non-hold-open handle, which prevents toilet from exceeding intended flush volume
- Flush accuracy is controlled by CID™ technology, also enhancing water efficiency
- Integrity of the product is maintained with the vandal-resistant stop cap
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance
- Adjustable tailpiece
- PERMEX synthetic rubber diaphragm with Dual Filtered Fixed Bypass
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

**DOWNLOADS**

- [Royal Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Royal Flushometers Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • [sloan.com](http://sloan.com)

Angle Stop (YO)

**Pipe Support**

Solid Ring (YK)

Split Ring (YJ)

**Special Features**

Less Logo (LL)

Whitworth Thread (WWT)

**Compliances & Certifications**

BAA Compliant

ADA Compliant

cUPC Certified

UPC Certified

BREEAM Water Credit

Green Globes Water Credit

LEED V4 Water Efficiency Credit

Satisfies LEED Credits

WaterSense Listed

cUPC Green Certified

**NOTES**

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.