

► Code Number
3012660

► SPECIFICATIONS

Description

Exposed, Battery Powered, Sensor Activated, Sloan® Optima® SMOOTH® Urinal Flushometer for ¾" top spud urinals.

Flush Cycle

1.5 gpf / 5.7 lpf

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

FLUSHOMETER

- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- ADA Compliant Metal Oscillating Non-Hold-Open Handle with Triple Seal Handle Packing
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Flush Accuracy Controlled by CID Technology
- ¾" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Spud Coupling and Flange for ¾" Top Spud
- Diaphragm, Handle Packing, Stop Seat and Vacuum Breaker molded from PERMEX® Rubber Compound for Chloramine Resistance
- "User in View" Flashing LED
- Sweat Solder Adapter w/Cover Tube and Cast Wall Flange w/Set Screw

Optima SMOOTH Unit

- ADA Compliant OPTIMA® SMOOTH™ Infrared Sensor for automatic "Hands-free" operation
- Sensor with Automatic Range Adjustment
- Chrome Plated Metal Sensor Housing
- Mechanical Manual Override Flush Handle
- 25 to 80 psi Operating Range

Valve Body, Cover and Tailpiece shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

Fixtures

Consult factory for matching Sloan brand fixture options.

Accessories (Sold Separately)

- See Accessories Section and Royal® Optima® SMOOTH® Flushometer Accessories Section of the Sloan catalog for details on these and other Royal® Optima® Flushometer Accessories.



► FEATURES

Automatic Operation

- SMOOTH® Hardwire equipped Flushometers provide the ultimate in sanitary protection and automatic operation. Once the user enters the sensor's effective range and then steps away, the SMOOTH® Unit initiates the flushing cycle to flush the fixture. State-of-the-art Technology enables override activation without "double flushing" as the user departs (sensor is locked-out for approximately 10 seconds). True manual override eliminates the need for expensive battery back-up systems.

Economical

- Automatic operation provides water usage savings over other flushing devices. Reduces maintenance and operation costs. Installation does not require turning off water to the valve.

Hygienic

- The Royal® Optima® SMOOTH™ Flushometer is the next advancement in hygiene. It uses sensor technology to transform manual installations into electronic, hands-free operation. User makes no physical contact with the Flushometer surface except to initiate the Override Handle when required. Helps control the spread of infectious diseases.

► Compliance & Certifications



This space for Architect/Engineer Approval

► ELECTRICAL SPECIFICATIONS

Control Circuit

- 6 VDC Input

Sensor Type

- Active Infrared with Automatic Adjustment

Sensor Range

- Normal Range: 26" - 32" (660 mm-813 mm)
- Reduced Range: 20" - 26" (508 mm-660 mm)

Indicator Lights

- User in View


Operating Pressure

- 25-80 psi (172-552 kPa)


► OPERATION



1. A continuous, invisible light beam is emitted from the SMOOTH™ unit's Infrared Sensor.



2. When the user enters the sensor's effective range, the Red LED light in the sensor window flashes for eight seconds. After eight seconds of sensing the user, the light will stop flashing and the unit waits for the user to step away before initiating a flush cycle.



3. When the user steps away, the unit initiates a flush cycle. The unit then automatically resets and is ready for the next user.

► ROUGH-IN

