

Part No: 4423-040C

Valves

Industrial Swing Check Valve

Desc: 4 CPVC SWING CHECK VALVE FLANGED EPDM

MSRP: 5925.66

Part Code: 111

Weight(lbs): 20.357

Weight(kg): 9.234

Weight(gm): 9234

Size: 4"


Color: GRAY

Material: CPVC

Type Standard

O-Ring EPDM

Pressure Rating 150 PSI @ 73° F



A = 11- 3/4

B = 11-13/16

C = 9

D = 3-29/32

E = 7- 1/4

F = 9- 1/2

Bolt = 7- 1/2  
Circle  
Dia.

Bolt Size = 3/4

I = 31/32

Cv = 480  
Values

No of  
Bolts = 8

G = 4- 1/2

H = 3-17/32

**Injection Molded Dimension References:**

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch


L = Overall length of fittings; ± 1/16 inch.

M = Outside diameter of socket/thread hub; ± 1/16 inch.

N = Socket bottom to socket bottom; couplings; ± 1/16 inch.

W = Height of cap; ± 1/16 inch

**Typical Molded Dimension References**



The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained therefrom. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006