Spears® Technical Information

17-Aug-21 01:55:00 AM


Part No: 853-240F Fabricated Fittings Flanges and Cut in Kits

Desc: 24 PVC BLIND FLANGE 50PSI FAB

MSRP: 6746.41 **Part Code:** 083

Weight(lbs): 65.257 Weight(kg): 29.6 Weight(gm): 29600
Size: 24" Color: GRAY Material: PVC

Joint Style Blind
Connection Blind
Ring Plastic



O.D. = 32

 $\mathbf{R} = 1 - 1/2$

 $\begin{array}{l} \textbf{No of} = 20 \\ \textbf{Bolts} \end{array}$

Bolt = 29- 1/2 **Circle**

Bolt Size = 1 - 1/4

Dia.

 $\begin{array}{ll} \textbf{Min. Bolt} &=& 5\text{-}1/2\\ \textbf{Length} & \end{array}$

Fabricated Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/4$ & larger $\pm 1/2$ inch.

H = Intersection of center lines to face of fitting; 90° elbows, tees, crosses; $\pm 1/4$ inch.; wyes $\pm 1/2$ inch; 14" & larger inch

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/4$ inch; 14'' & larger $\pm 1/2$ inch.


L = Overall length of fittings; $\pm 1/2$ inch; wyes ± 1 inch; 14" & larger ± 1 inch.


 $M = Outside diameter of socket/thread hub; <math>\pm 1/4$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/2$ inch.


W = Height of cap; $\pm 1/4$ inch.

Typical Fabricated Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006