Spears® Technical Information

12-Aug-21 04:41:23 AM

Part No: 867-666SR Schedule 80 PVC & CPVC Clamp-On Saddle

Desc: 12X6 PVC CLAMP SADDLE SRFPT EPDM ZNC BLT


MSRP: 730.32 Part Code: 086

Weight(lbs): 17.238 Weight(kg): 7.819 Weight(gm): 7819
Size: 12"X6" Color: GRAY Material: PVC

Size: 12"X6" Color: GRAY Ma

Connection Single SR Fipt **Type** Clamp Saddle

Hardware Zinc
O-Ring EPDM



$$\mathbf{H} = 10-9/32$$

$$H1 = 7-1/8$$

$$\mathbf{L} = 8 - 1/2$$

$$L1 = 14-1/4$$

$$M = 7-21/32$$

$$N = 2-3/8$$

Hole Size
$$= 6$$

$$\begin{array}{c} \textbf{Bolt} = 10 \\ \textbf{Torque} \end{array}$$

$$\mathbf{No of} = 6$$

Torque FT./LBS.

No of a

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/32$

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; $\pm 1/32$ inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/32$ inch


L = Overall length of fittings; $\pm 1/16$ inch.


M = Outside diameter of socket/thread hub; $\pm 1/16$ inch.


N = Socket bottom to socket bottom; couplings; $\pm 1/16$ inch.


W = Height of cap; $\pm 1/16$ inch

Typical Molded Dimension References









The information printed here is based on current information & product design at the time of publication and is subject to change without notification. Spears® ongoing commitment to product improvement may result in some variation. No representation, guarantees or warranties of any kind are as to its accuracy, suitability for particular application or results to be obtained thereform. For verification of technical data or additional information, please contact Spears® Technical Service Department :: WEST COAST : (818) 364-1611 - EAST COAST : (717) 938-9006