

Part No: HT2S-334

Schedule 80 PVC & CPVC

Hot-Tap Saddle

Desc: 3X3/4 PVC HOT TAP SADDLE EPDM S/S BOLT

MSRP: 163.79

Part Code: 049

Weight(lbs): 1.351


Weight(kg): 0.613

Weight(gm): 613

Size: 3 X 3/4 SOC(1"SPG)

Color: GRAY

Material: PVC



H1 = 2

H2 = 2

M = 2

L1 = 4-3/4

L = 3

G = 3-15/16

G1 = 1

H = 6-5/8

Connection Saddle x Socket (Spigot)

Hardware SS316

O-Ring EPDM

NOTE Not intended To Convey Or
Dispense Water For Human
Consumption Through Drinking
Or Cooking

Cutter Brass

Type Hot-Tap

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/32$ inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; $\pm 1/32$ inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/32$ inch

L = Overall length of fittings; $\pm 1/16$ inch.

M = Outside diameter of socket/thread hub; $\pm 1/16$ inch.

N = Socket bottom to socket bottom; couplings; $\pm 1/16$ inch.

W = Height of cap; $\pm 1/16$ inch

Typical Molded Dimension References

