

Part No: HTS3S-337

Schedule 80 PVC & CPVC

Hot-Tap Saddle

Desc: 3X1-1/2 PVC HOT TAP SADDLE FKM SS CUTTER

MSRP: 1008.1

Part Code: 049

Weight(lbs): 2.917


Weight(kg): 1.323

Weight(gm): 1323

Size: 3 X 1-1/2 SOC (2"SPG)

Color: GRAY

Material: PVC



L = 4-1/8

L1 = 4-3/4

G = 5-1/8

G1 = 1-1/4

H = 9-1/8

H1 = 2-11/16

H2 = 2

M = 2-7/8

Connection Saddle x Socket (Spigot) - LEAD FREE

Hardware SS316

O-Ring FKM

Cutter SS316

Type Hot-Tap

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; $\pm 1/32$ inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; $\pm 1/32$ inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; $\pm 1/32$ inch

L = Overall length of fittings; $\pm 1/16$ inch.

M = Outside diameter of socket/thread hub; $\pm 1/16$ inch.

N = Socket bottom to socket bottom; couplings; $\pm 1/16$ inch.

W = Height of cap; $\pm 1/16$ inch

Typical Molded Dimension References

