

Part No: S1720-25

Valves

Swing & Spring Check

Desc: 2-1/2 PVC T/U UTILITY SW CK VLV SOC EPDM

MSRP: 99.14

Part Code: 026

Weight(lbs): 5.631

Weight(kg): 2.554

Weight(gm): 2554

Size: 2-1/2"

Color: WHITE


Material: PVC

Type Utility Swing Check

Connection Socket (TU)

Body Color White

Pressure Rating 150 psi @ 73° F Full Flow (Open)
75 psi Back Pressure (Closed)



A = 6-3/16

B = 7-13/32

C = 10-15/16

D = 5-3/4

Injection Molded Dimension References:

G = (LAYING LENGTH) intersection of center lines to bottom of socket/thread; 90° elbows, tees, crosses; ± 1/32 inch.

H = Intersection of center lines to face of fitting; 90° elbows tees, crosses; ± 1/32 inch.

J = Intersection of center lines to bottom of socket/thread; 45° elbows; ± 1/32 inch

L = Overall length of fittings; ± 1/16 inch.

M = Outside diameter of socket/thread hub; ± 1/16 inch.

N = Socket bottom to socket bottom; couplings; ± 1/16 inch.

W = Height of cap; ± 1/16 inch

Typical Molded Dimension References

