
TAG:	


Single Pantry Faucet

Architect/Engineering Specifications:

Single hole single temperature deck mount faucet with polished chrome plated brass body, swivel vacuum beaker nozzle with 3/8" NPT stainless steel quick disconnect outlet, 3/8" vacuum breaker, ceramic cartridge with check valve, lever handle and 1/2" NPSM male inlet. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.

Job Name______Quantity_____Variations Specified______Date_







Features & Benefits:

- Single hole single temperature deck mount faucet w/ polished chrome plated brass body
- Swivel vacuum beaker nozzle
- · Lock washer provided for rigid application
- 3/8" NPT stainless steel quick disconnect outlet w/ 3/8" compression male thread connection
- 3/8" vacuum breaker
- · Quarter-turn Cerama cartridge w/ check valve
- · Lever handle w/ blue index
- Ø2" flange w/ 1/2" NPSM male inlet
- Tailpiece and nut to provide 1/4" NPT male connection
- Material: Polished chrome plated brass body & tubular spout and polished chrome plated metal handle

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)

Cerama Cartridge: Lifetime (Limited)

Performance Data:

Pressure: 20 - 125 psi
Temperature: 40 °F - 140 °F
Flow Rate: 4.06 GPM @ 60 psi







Optional Cartridges With Checks

- □ Quarter-Turn Cerama w/ Check Valve (Standard)
- □ Quarter-Turn Eterna w/ Spring Check

Optional Handles

- □ 4" Wrist Action
- □ Lever (Standard)
- □ 4-Arm







T&S BRASS AND BRONZE WORKS, INC.

