

SPECIFICATIONS FOR AQUANOT MAINTENANCE FREE BATTERIES:

BCI Group	Model Description	Electrical Capacity			Inches			Millimeters			Terminal Torque		Weight	
		Nominal Voltage	Ah Capacity	RC Minutes	L	W	н	L	w	Н	in-lbs	Nm	Lbs	Kgs
FLOOD	FLOODED MAINTENANCE FREE BATTERY Stainless Threaded Terminal													
27	10-5105	12	90	140	12.95	6.81	9.38	329	173	238	100-120	11-14	53	24.0
31	10-0761	12	100	180	13.00	6.75	9.38	330	171	238	100-120	11-14	58	26.3
AGM N	AGM MAINTENANCE FREE BATTERY Stainless Threaded Terminal													
27	10-1450	12	100	180	12.05	6.65	9.13	306	169	232	100-120	11-14	57	26.0



FLOODED MAINTENANCE FREE **BACKUP POWER BATTERIES**

Aquanot® Flooded Maintenance Free Batteries feature a proven flooded battery design – with advanced features like SolidCast™ plates, PosiWrap™ plate separators and oversized top-lead and terminal post connections to provide durability and efficiency in standby back-up pump applications. Aquanot® Maintenance Free Batteries are built for applications where reliable maintenancefree service is a requirement, and have a useful life of 3 to 4 years.

Run Time and Gallons Pumped

508 pump	Estimate	d Hours	Estimated gallons				
paired with:	Continuous	10% Duty					
10-1450	5.5	55	11550				
10-0761	5.5	55	11550				
10-5105	5	50	10500				

The 507 pump has lower amps so will run longer. But it isn't as efficient causing total gallons to be much less than the 508.

10-5184 - Dual Battery Kit. Includes additional battery box and heavy gauge jumper wires.



AGM MAINTENANCE FREE BACKUP POWER BATTERY

Aquanot® AGM Batteries feature a sealed, maintenancefree design that delivers absolute dependability, zero battery off-gassing in standard charging conditions and easy installation and inspection. Aquanot® batteries are purpose-built backup power solutions that work precisely with backup pump and other UPS applications – and feature a sealed design with robust internal construction to deliver reliable, maintenance-free backup power on demand. The product's design also includes endurance features such as high-strength glass mat separators that ensure a quick recovery from deep discharge – and is designed to deliver a useful life of 4 to 5 years.



3649 Cane Run Rd. | Louisville, KY 40211 | +1.502.778.2731 zcotechnical@zoeller.com | www.zoellerpumps.com