



Sizing and Selection Chart 25P, 25PE, 25PA, and all Combinations

Capacities

Inlet Steam Pressure psig	Outlet Steam Pressure psig	NOMINAL VALVE SIZE									
		1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
	C.V. Factors \bar{I}	3.48	6.5	10.5	14	20	35	56	74	115	280
15	10	95	175	285	380	540	950	1,500	2,000	3,100	7,140
	5	135	250	405	545	780	1,365	2,185	2,890	4,480	10,373
	3	155	285	465	620	880	1,550	2,470	3,260	5,080	11,669
20	12	120	230	365	490	700	1,225	1,960	2,590	4,025	9,282
	8	155	290	470	630	900	1,575	2,520	3,330	5,175	11,934
	0-5	180	335	540	720	1,025	1,795	2,870	3,790	5,895	13,592
25	15	145	270	435	580	830	1,450	2,325	3,070	4,770	11,006
	10	195	360	580	775	1,110	1,950	3,110	4,110	6,385	14,719
	0-7	205	385	620	825	1,180	2,065	3,305	4,360	6,785	15,647
30	20	155	290	470	630	900	1,575	2,520	3,330	5,175	11,934
	15	220	410	665	890	1,270	2,220	3,555	4,700	7,300	16,840
	0-12	230	430	695	925	1,320	2,310	3,695	4,885	7,590	17,503
40	30	155	290	470	630	900	1,575	2,520	3,330	5,175	11,934
	25	250	470	755	1,010	1,440	2,520	4,030	5,330	8,280	19,094
	0-18	280	525	850	1,135	1,620	2,835	4,535	5,995	9,315	21,481
50	40	190	355	575	770	1,100	1,925	3,080	4,070	6,325	14,586
	30	315	585	955	1,275	1,820	3,185	5,095	6,735	10,465	24,133
	0-21	350	650	1,050	1,400	2,000	3,500	5,600	7,400	11,500	26,520
60	45	280	520	840	1,120	1,600	2,800	4,480	5,920	9,200	21,216
	35	360	670	1,080	1,440	2,060	3,605	5,770	7,620	11,845	27,316
	0-27	385	720	1,165	1,555	2,220	3,885	6,215	8,215	12,765	29,437
75	60	280	525	850	1,135	1,620	2,835	4,535	5,995	9,315	21,481
	50	415	775	1,250	1,665	2,380	4,165	6,665	8,800	13,685	31,559
	0-35	470	875	1,415	1,890	2,700	4,725	7,560	9,990	15,525	35,802
85	70	290	540	870	1,160	1,660	2,905	4,650	6,140	9,545	22,012
	50	490	915	1,480	1,965	2,820	4,935	7,895	10,435	16,215	37,393
	0-43	515	960	1,555	2,070	2,960	5,180	8,290	10,950	17,020	39,250
100	80	370	690	1,115	1,485	2,120	3,710	5,935	7,845	12,190	28,111
	60	580	1,080	1,740	2,325	3,320	5,810	9,295	12,285	19,090	44,023
	0-48	600	1,120	1,815	2,420	3,460	6,055	9,690	12,800	19,895	45,900
125	100	440	825	1,335	1,780	2,540	4,445	7,110	9,400	14,600	33,660
	80	680	1,275	2,060	2,745	3,920	6,860	10,975	14,500	22,540	51,979
	0-62	730	1,365	2,200	2,940	4,200	7,350	11,760	15,540	24,150	55,692
150	125	490	910	1,470	1,960	2,800	4,900	7,840	10,360	16,100	37,128
	100	800	1,490	2,400	3,205	4,580	8,015	12,825	16,945	26,335	60,731
	0-76	860	1,600	2,590	3,460	4,940	8,645	13,830	18,280	28,400	65,504
175	150	490	915	1,480	1,975	2,820	4,935	7,895	10,435	16,125	37,393
	125	870	1,630	2,635	3,515	5,020	8,785	14,055	18,570	28,865	66,565
	0-87	985	1,840	2,970	3,960	5,660	9,900	15,850	20,950	32,545	75,052
200	150	840	1,600	2,540	3,390	4,840	8,470	13,550	17,900	27,830	67,238
	125	1,075	2,000	3,240	4,330	6,180	10,815	17,300	22,870	35,530	81,947
	0-103	1,125	2,100	3,390	4,520	6,460	11,300	18,000	23,900	37,145	85,660
225	175	840	1,650	2,670	3,560	5,080	8,890	14,225	18,800	29,210	67,320
	150	1,160	2,180	3,500	4,660	6,660	11,655	18,650	24,640	38,300	88,332
	0-117	1,250	2,340	3,780	5,000	7,200	12,600	20,160	26,640	41,400	95,472
250	200	925	1,730	2,790	3,720	5,320	9,300	14,900	19,680	30,600	70,584
	150	1,340	2,500	4,050	5,400	7,720	13,500	21,600	28,600	44,400	102,367
	0-131	1,385	2,590	4,180	5,570	7,960	13,930	22,300	29,450	45,800	105,570
*273	225	880	1,640	2,650	3,530	5,050	8,830	14,130	18,670	29,000	67,320
	200	1,240	2,320	3,750	4,990	7,130	12,480	19,960	26,400	41,000	95,000
	0-145	1,510	2,830	4,570	6,090	8,700	15,230	24,360	32,200	50,000	
*300	250	920	1,720	2,780	3,700	5,290	9,250	14,800	19,600	30,400	70,584
	225	1,250	2,330	3,770	5,020	7,170	12,550	20,100	26,500	41,300	95,000
	0-160	1,640	3,070	4,960	6,600	9,440	16,520	26,400	34,900	54,300	

Capacities are based on an accuracy regulation of 1 PSI and with pipe sizes to insure reasonable velocities. Refer to pipe sizing chart. * Cast steel construction required for service above 250 psig

Local regulation may restrict the use of this product below the conditions quoted. Limiting conditions refer to standard connections only.

In the interests of development and improvement of the product, we reserve the right to change the specification.